

Anson Successfully “Polishes” Green River Lithium Chloride

ASX: **ASN** Announcement

Highlights:

- “Polishing” has successfully reduced the minor contaminants remaining in the pure Lithium Chloride eluate, ready for final evaporation and crystallization to lithium carbonate,
- Polishing process flowsheet was developed and tested at Anson’s Lithium Innovation Center, USA
- Process uses nanofiltration, reverse osmosis and a combination of IX systems, which are manufactured in the USA,
- The polishing system has been installed at the Green River and is in continuous operation processing the 43,000 gallons of eluate produced by the Koch’s DLE system,
- On track to produce battery grade lithium carbonate with final evaporation and carbonation steps

Anson Resources Limited (ASX: **ASN**) (“**Anson Resources**” or the “**Company**”) through its 100% owned subsidiary Blackstone Minerals NV LLC is pleased to announce that it is continuing the “polishing” program of the highly purified lithium chloride eluate (LiCl) produced at the Green River Lithium Project, south eastern Utah, USA, using the Koch Technology Services (“**KTS**”) Direct Lithium Extraction (“**DLE**”) pilot plant, see *ASX Announcement 28 March 2025 and 9 April 2025*.

“Polishing” is the first and a critical step in the downstream processing which further removes minor contaminants remaining in the purified lithium chloride eluate after the DLE process prior to the final steps of evaporation and carbonation. The majority of the contaminants are removed in the DLE process. These contaminants if not removed can result in a lower grade final lithium carbonate product. An efficient “Polishing” step can beneficially impact the Capex and OPEX of a Lithium Carbonate Plant.

The “polishing” process, developed by A1 Technologies Inc (see ASX Announcement 9 April 2025), has proved a major success removing the cations that could affect the lithium carbonate product in the downstream processing, see Table 1.

Product	Cations							
	B	Ba	Ca	K	Mg	Si	Cu	Zn
LiCl Eluate	11.68	2.37	41.83	28.88	13.28	4.72	2.11	3.14
Polished Eluate	0.56	0	1.134	4.15	0	1.05	0	0
Rejection Rate (%)	96.3	100	98.3	89.9	100	76.8	100	100

Table 1: The rejection rates of the minor contaminants left in the eluate after completion of the DLE process.

Downstream of the polishing processes, the LiCl solution is concentrated with various off the shelf technologies, including nanofiltration and reverse osmosis, to further remove the minute unwanted impurities (e.g. calcium, potassium, magnesium, boron, etc.).

Anson's wholly owned subsidiary company A1 Technologies Inc's Lithium Innovation Center has been trialing several of the available technologies and has developed a downstream processing flowsheet suitable for the processing of the 43,500 gallons of LiCl that was produced by the KTS pilot plant at the Green River Sample Demonstration Plant (SDP), see Figure 1.




Figure 1: Flowsheet showing the DLE and downstream processes used to produce lithium carbonate.

The initial polished samples from the Green River SDP have been completed and are being concentrated prior to the final steps of evaporation and carbonation when the remaining contaminants either precipitate or washed out to produce EV grade lithium carbonate.

This announcement has been authorized for release by the Executive Chairman and CEO.

ENDS

For further information please contact:

Bruce Richardson
Executive Chairman and CEO
E: Info@AnsonResources.com
Ph: +61 7 3132 7990
www.AnsonResources.com

Will Maze
Head of Investor Relations
E: Investors@AnsonResources.com
Ph: +61 7 3132 7990

Follow us on Twitter @Anson_ir

Subscribe to Anson Resources News: [Click Here](#)

Forward Looking Statements: Statements regarding plans with respect to Anson's mineral projects are forward-looking statements. There can be no assurance that Anson's plans for development of its projects will proceed as expected and there can be no assurance that Anson will be able to confirm the presence of mineral deposits, that mineralization may prove to be economic or that a project will be developed.

Competent Person's Statement 1: The information in this announcement that relates to exploration results and geology is based on information compiled and/or reviewed by Mr Greg Knox, a member in good standing of the Australasian Institute of Mining and Metallurgy. Mr Knox is a geologist who has sufficient experience which is relevant to the style of mineralization under consideration and to the activity being undertaken to qualify as a "Competent Person", as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves and consents to the inclusion in this report of the matters based on information in the form and context in which they appear. Mr Knox is a director of Anson.

About Anson Resources Ltd

Anson Resources (ASX: ASN) is an ASX-listed mineral resources company with a portfolio of minerals projects in key demand-driven commodities. Its core assets are the Green River and Paradox Lithium Project in Utah, in the USA. Anson is focused on developing these assets into a significant lithium producing operations. The Company's goal is to create long-term shareholder value through the discovery, acquisition and development of natural resources that meet the demand of tomorrow's new energy and technology markets.

JORC Code 2012 “Table 1” Report

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code Explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> Nature and quality of sampling (e.g. cut channels, random chips, or specific specialized industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc.). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralization that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverized to produce a 30 g charge for fire assay'). In other cases, more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralization types (e.g. submarine nodules) may warrant disclosure of detailed information. 	<ul style="list-style-type: none"> Raw brine was collected directly from the well and stored in a 16,000-gallon tank. Samples were collected in 250ml clean plastic sample bottles at the well, from the storage tanks, eluate tanks and spent brine tanks. Each bottle was marked with the location, date and time sampled. Duplicate samples were also collected and securely stored. Samples were delivered to certified laboratory off site (SGS in Texas) to compare with the onsite ICP assay results The samples sizes (250ml for each individual sample) are considered to be appropriate for the material being tested.
Drilling Techniques	<ul style="list-style-type: none"> Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc.) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face sampling bit or other type, whether core is oriented and if so, by what method, etc.). 	<ul style="list-style-type: none"> The Bosydaba #1 well was drilled in 2024, see ASX Announcement 22 April 2024.
Drill Sample Recovery	<ul style="list-style-type: none"> Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	<ul style="list-style-type: none"> Brine has been continuously collected when required for geochemical processing. 600 barrels (100 barrels per truck load) of raw brine was collected and stored in a raw brine tank on site at the demonstration plant which is located 200m north of the Bosydaba#1 well. “Swabbing” (brine extraction) occurred fortnightly. Sampling of each truckload was carried out. During the fine tuning stages of the process, samples were collected daily from the storage tanks.
Logging	<ul style="list-style-type: none"> Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography. The total length and percentage of the relevant intersections logged. 	<ul style="list-style-type: none"> No logging has been completed as it is not a new well, completed while drilling the well, see ASX Announcement 22 April, 2024.

Criteria	JORC Code Explanation	Commentary
Sub-sampling Techniques and Preparation	<ul style="list-style-type: none"> • If core, whether cut or sawn and whether quarter, half or all core taken • If non-core, whether riffled, tube sampled, rotary split, etc. and whether sampled wet or dry. • For all sample types, the nature, quality and appropriateness of the sample preparation technique. • Quality control procedures adopted for all sub-sampling stages to maximize representivity of samples. • Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling. • Whether sample sizes are appropriate to the grain size of the material being sampled. 	<ul style="list-style-type: none"> • Samples were submitted to Laboratories in Texas, USA that are certified and experienced with oilfield brines • Each sample bottle was taped and marked with the sample number. • The sample sizes (4 * 250ml) are considered to be appropriate for the brine being sampled. • Sample preparation techniques represent industry good practice.
Quality of Assay Data and Laboratory Tests	<ul style="list-style-type: none"> • The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. • For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. • Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established. 	<ul style="list-style-type: none"> • Laboratory testing was carried out using ICP-OES. • SGS is ISO9001 certified and specializes in oil field brines. • The ICP-OES machines continuously tested with standards made up by chemical laboratories for each of the minerals being tested. • Multiple samples were collected to confirm assay results (duplicates). • Sample analysis showed no large discrepancies.
Verification of Sampling and Assaying	<ul style="list-style-type: none"> • The verification of significant intersections by either independent or alternative company personnel. • The use of twinned holes. • Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. • Discuss any adjustment to assay data. 	<ul style="list-style-type: none"> • Sampling and assaying were carried out on site. • Assaying technique used was ICP-OES which is suitable for this sample type. • Stable blank samples (RO water) were regularly tested to evaluate potential sample contamination. • Regular calibration using standard buffers were continuously carried out.
Location of Data Points	<ul style="list-style-type: none"> • Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. • Specification of the grid system used. • Quality and adequacy of topographic control. 	<ul style="list-style-type: none"> • The grid system used is UTM Zone 12 (NAD83). • Location of drillhole was positioned by a qualified land surveyor. • Drillhole collar LAT: 38.874904° (4,303,268.5N) LON: -110.113014° (576,941.41E) EL: 4125.7' Dip: -90° Azim: 0°
Data Spacing and Distribution	<ul style="list-style-type: none"> • Data spacing for reporting of Exploration Results. • Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. • Whether sample compositing has been applied. 	<ul style="list-style-type: none"> • There has been no compositing of brine samples.

Criteria	JORC Code Explanation	Commentary
<i>Orientation of Data in Relation to Geological Structure</i>	<ul style="list-style-type: none"> Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralized structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	<ul style="list-style-type: none"> The Paradox Basin hosts bromine and lithium bearing brines within a sub-horizontal sequence of salts, anhydrite, shale and dolomite. The Bosydaba#1 well has a vertical (dip -90), perpendicular to the target brine hosting sedimentary rocks.
<i>Sample Security</i>	<ul style="list-style-type: none"> The measures taken to ensure sample security. 	<ul style="list-style-type: none"> Samples were transported to laboratories on collection at the well.
<i>Audits or Reviews</i>	<ul style="list-style-type: none"> The results of any audits or reviews of sampling techniques and data 	<ul style="list-style-type: none"> No audits or reviews have been conducted at this point in time.

Section 2 Reporting of Exploration Results

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code Explanation	Commentary
<i>Mineral Tenement and Land Tenure Status</i>	<ul style="list-style-type: none"> Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a license to operate in the area. 	<ul style="list-style-type: none"> The Green River Lithium Project is located in southeastern Utah, USA, consisting of 628 placer claims that encompasses a land position of 5,024 hectares (12,414.6 acres). Purchased private property consists of a 59.6-hectare (147.5 acre) land parcel 1 OBA lease 2,750 hectares (6,795.4 acres). All claims are held 100% by Anson's U.S. based subsidiary, Blackstone Minerals NV LLC. The claims/leases are in good standing, with payment current to the relevant governmental agencies.
<i>Exploration Done by Other Parties</i>	<ul style="list-style-type: none"> Acknowledgment and appraisal of exploration by other parties. 	<ul style="list-style-type: none"> Historical exploration for brines within the Paradox Basin includes only limited work in the 1960s. No historical economic production of bromine or lithium from these fluids has occurred in the project area. The historical data generated through oil and gas development in the Paradox Formation and the Leadville Limestone unit has supplied some information on brine chemistry.
<i>Geology</i>	<ul style="list-style-type: none"> Deposit type, geological setting and style of mineralization. 	<ul style="list-style-type: none"> The geology of the Paradox Formation indicates a restricted marine basin, marked by 29 evaporite sequences. Brines that host bromine and lithium mineralization occur within the saline facies of the Paradox Formation and are generally hosted in the more permeable dolomite sediments. The Leadville Limestone consists of dolomite and limestone which hosts the supersaturated brines.

	Criteria	JORC Code Explanation	Commentary
	Drill Hole Information	<ul style="list-style-type: none"> A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> easting and northing of the drill hole collar elevation or RL (Reduced Level - elevation above sea level in meters) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	<ul style="list-style-type: none"> The grid system used is UTM Zone 12 (NAD83). Location of drillhole was positioned by a qualified land surveyor. Drillhole collar LAT : 38°58'56.85510" LON : -110°08'35.14421" EL : 4070 Dip - -90° AZIM - 0°
	Data Aggregation Methods	<ul style="list-style-type: none"> In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade Brine samples taken in holes were averaged (arithmetic average) without 14 Criteria JORC Code explanation Commentary truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	<ul style="list-style-type: none"> No weighting has been carried out.
	Relationship Between Mineralization Widths and Intercept Lengths	<ul style="list-style-type: none"> These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralization with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known'). 	<ul style="list-style-type: none"> Brines are collected and sampled over the entire perforated width of the zone. The Mississippian Units are assumed to be porous and permeable over its entire vertical width based on drilling records.
	Diagrams	<ul style="list-style-type: none"> Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	<ul style="list-style-type: none"> Not Applicable.
	Balanced Reporting	<ul style="list-style-type: none"> Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	<ul style="list-style-type: none"> Not Applicable.

Criteria	JORC Code Explanation	Commentary
<i>Other Substantive Exploration Data</i>	<ul style="list-style-type: none"> Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples - size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	<ul style="list-style-type: none"> All available new geochemical data has been presented.
<i>Further Work</i>	<ul style="list-style-type: none"> The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	<ul style="list-style-type: none"> The future well and sampling planned will cover the Leadville Limestone. Future wells will focus on the current well surrounding the proposed locations to upgrade the JORC resource.